



## Electrician's Flex Bit With Screw Point - Stretch Bit

Part #	Size	X	OAL	Shank	Application
308FB2438	3/8"	X	24"	3/16"	Popular with alarm & communication installers for pulling light wire.
308FB3638	3/8"	X	36"	3/16"	
308FB5438	3/8"	X	54"	3/16"	
308FB7238	3/8"	X	72"	3/16"	
308FB2412	1/2"	X	24"	3/16"	Popular with alarm & communication installers for pulling light wire.
308FB3612	1/2"	X	36"	3/16"	
308FB5412	1/2"	X	54"	3/16"	
308FB7212	1/2"	X	72"	3/16"	



Wood Plywood Drywall

- ◆ Screw Point
- ◆ Self Drilling
- ◆ Fish Hole On Each End
- ◆ Flexible Shaft
- ◆ Sold Individually



FISH HOLE ON SHANK



Stretch Bits are constructed of a high carbon steel self-feed auger bit, permanently brazed to a flexible shaft. This tool can be inserted through small wall openings enabling the operator to bore holes through studs within the wall cavities without damaging finished walls or ceilings.

Eye Holes are provided at each end of the Stretch Bits which allow easy retrieval of wires from either direction after drilling.

## Steering Guide

Part #	Description	Application
308FBG	Steering Guide	Helps manipulate bits while within the wall cavity.




## Circular Saw Blades

Part #	Size	Box Qty.
DS-58-724	7-1/4" X 24T	25
CS-58-824	8-1/4" X 24T	25
CS-58-840	8-1/4" X 40T	25



Wood Plywood

- ◆ Tungsten Carbide Tipped
- ◆ 5/8" Arbor With Diamond Knock Out
- ◆ 7000 RPM Maximum
- ◆ Hard Body 38-42 Rc.
- ◆ K20 Tungsten Carbide Grade
- ◆ Individually Protected
- ◆ Individually Barcoded
- ◆ Imported



ALTERNATE TOP BEVELED TEETH

