



J e t - L u b e o f C a n a d a L t d .

# AGRICULTURE

Anti-Seize, Sealants and Lubricants





# AGRICULTURE

Anti-Seize, Sealants and Lubricants

## Featured Products

- 12/34** - Lubricant and Penetrant
- #202 Moly-Lith** - Premium Multi-Purpose Grease with MoS<sub>2</sub>
- Alco-EP** - Premium Multi-Purpose Grease
- AP-5** - High Temperature Grease with Molybdenum Disulphide
- CB-2** - Super Lithium Multi-Purpose Grease
- Creeper-Lube** - Multi-Purpose Grease
- Gear-Guard** - Paste Open Gear Lubricant
- JetPump** - Two-Stage Hydro-Test Pump
- Kopr-Kote HT** - High Temperature Anti-Seize
- Moly Mist** - MoS<sub>2</sub> Dry Film Lubricant
- No. 33** - Premium Silicone Thickened Lithium Grease
- OG-H** - Open Gear Lubricant
- Petro-Tape** - PTFE Thread Seal Tape
- Renew** - Belt Dressing
- RuFF** - Heavy-Duty Rust and Corrosion Inhibitor
- Silicone Spray** - Industrial Grade Lubricant
- TF-15** - Thread Sealing Compound
- Top-Gun** - Wasp and Hornet Killer
- White Lithium Grease** - All-Purpose Grease with PTFE

## 12/34 Lubricant and Penetrant



**Operating Range** -75°C to 150°C (-100°F to 300°F)

The foremost penetrating, moisture displacing, lubricating and corrosion preventative available today! Unequaled where salt water, salt spray or other harsh environments are encountered. Provides superior protection and anti-wear properties, penetrates into rusted, corroded and frozen metal parts, which will be easily loosened by means of superior 'creepability', removes moisture; prevents rust and corrosion.

SKU #	Size
37341	340 g aerosol
37343	500 ml trigger spray
37316	4 liter can
37320	20 liter pail
37375	205 liter drum

## #202 Moly-Lith Premium Multi-Purpose Grease with MoS<sub>2</sub>



**Operating Range** -18°C to 150°C (0°F to 300°F)

An all-weather product with exceptional resistance to the effects of water, weathering, oxidation and heavy loads. Gives excellent protection wherever dirt, dust, high humidity, rain and adverse temperatures are critical problems. Can also be used as a general chassis lubrication.

SKU #	Size
33050	14 oz cartridge
33019	35 lb pail
33055	55 liter keg

## Alco-EP Premium Multi-Purpose Grease



**Operating Range** -32°C to 232°C (-25°F to 450°F)

Designed for friction and anti-friction bearings, bushings, chassis points, U-joints, pivot pins and a wide range of other fleet and equipment applications. Provides superior wear protection against extreme pressure and is highly water resistant.

SKU #	Size
37050	14 oz cartridge
37016	35 lb pail
37029	400 lb drum
37055	120 lb keg

## AP-5 High Temperature All-Purpose Grease



**Operating Range** -25°C to 288°C (-13°F to 550°F)

Recommended for use on ball, roller and sleeve bearings, shackles, conveyor chains, sealed assemblies, etc. Provides heavy-duty long-life protection in heavy equipment. When applied, it means that all your mechanical components, which are demanding superior lubrication, will last 2 to 10 times longer than when a regular grease has been applied. Especially recommended for lubrication points prone to neglect.

SKU #	Size
25067	250 ml squeeze tube
25050	400 g cartridge
25004	1 liter jar
25005	5 liter pail
25010	10 liter pail
25055	55 liter keg
25075	205 liter drum

## CB-2 Super Lithium Multi-Purpose Grease



**Operating Range** -18°C to 150°C (0°F to 300°F)

Specifically formulated for use on fast running bearings, anti-friction bearings, journals and all general greasing where a single multipurpose product is desired for economy, simplification of inventory and greasing equipment. Can be used as a chassis grease as well for all mobile machinery.

SKU #	Size
31050	14 oz cartridge
31003	1 lb brush top
31006	5 lb pail
31016	35 lb pail
31029	400 lb drum

## Creeper-Lube Multi-Purpose Lubricant



**Operating Range** -32°C to 177°C (-25°F to 350°F)

**SKU #** 88529  
**Size** 400 lb drum

To be used for gear and chain cases, speed reducers and transfer cases, where leakage, noise or wide temperature variations are present. Can also be utilized effectively in cotton spindles, track rolls, trailer landing gears, gang mower drives, etc. Creeper-Lube provides good pump-ability, high water resistance, and extreme pressure plus anti-wear properties.

## Gear-Guard Paste Open Gear Lubricant



**Operating Range** -32°C to 175°C (-25°F to 350°F)

**SKU #** 17905  
**Size** 9 lb pail  
17941 12 oz aerosol

To be used on open gears, roller gears, drive chains, fifth wheel of tractors and trucks, etc. Provides maximum lubrication and shock load protection, reduces gear noise, and prevents scoring and welding of gear teeth. Resists heat and pressure, will not wash or wear off because of weather, and will not break down after repeated workings. Is moisture resistant i.e., actually displacing water. The ideal product for fifth wheels of tractors and trucks.

## JetPump Two-Stage Test and Injection Pump



**Low Pressure/High-Volume for 0-300 psi High Pressure/Low-Volume for 0-5000 psi**

**SKU #** JP03  
**Size** 3-US gal  
JP05 5-US gal

JetPump advantage – High and low-pressure injection services, BOP testing, hydro testing and vessel testing just became easier with Jet-Lube's JetPump. These self-priming, two-stage pumps allow testing at either high or low pressures covering a wide range of applications. JetPump's non-pressurized body allows the tank to be refilled without depressurizing or disconnecting from the system every time – saving you time and money. Its stainless steel and aluminum construction eliminates corrosion and is light enough to be carried and rugged enough for industrial use.

## Kopr-Kote HT High Temperature Anti-Seize



**Operating Range** -54°C to 815°C (-65° to 1500°F)

**SKU #** 10250  
**Size** 400 g cartridge  
10202 225 ml brush top  
10203 450 ml brush top  
10204 1 liter jar

Recommended for use in production and maintenance jobs, where speed in assembling and dismantling is essential. Protects against seizure, heat-freeze, galling, rust and corrosion. Lowers friction, thus reducing wrench torques. Permits re-use of fittings, saving you money on stud, bolt and nut replacement. Is not affected by contraction, expansion or vibration.

## Moly Mist MoS<sub>2</sub> Dry Film Lubricant



**Operating Range** -185°C to 400°C (-300°F to 750°F)

**SKU #** 16041  
**Size** 340 g aerosol  
16015 35 lb pail  
16075 50-US gal drum

To be used wherever a dry lubricant is needed, particularly where temperatures are extreme, where environments are hostile, and where friction must be kept to a minimum. It lowers friction, prevents galling, seizure, stick-slip, fretting, corrosion and metal-to-metal contact. Reduces torque and power consumption. Can be used on chains, gears, or exposed surfaces where a dry lubricant is preferred to prevent a build-up of dirt and corrosion. **NOTE: not for use on oxygen lines.**

## No. 33 Premium Lithium Thickened Silicone Grease



**Operating Range** -57°C to 204°C (-70°F to 400°F)

**SKU #** 73850  
**Size** 14 oz cartridge  
73824 120 lb keg

Excellent for lubrication of ball and roller bearings under light loads, plastic and rubber parts, and small gears and applications requiring oxidation resistant lubrication. Especially effective in equipment that must start in extremely cold conditions.

## OG-H Open Gear Lubricant



Operating Range -18°C to 285°C (-0°F to 550°F)

To be used on applications which require a heavy-duty lubricant, such as exposed gears, steam and power winches, hoists, power shovels, etc. Can also be used wherever high unit pressures occur in slow-moving equipment. When applied, far less lubricant needs to be used versus competitive products, assuring greater economy.

SKU #	Size
26050	14 oz cartridge
26004	1 liter jar
26005	5 liter pail
26015	15 liter pail
17955	55 liter keg

## Petro-Tape PTFE Thread Seal Tape



Operating Range -240°C to 260°C (-400°F to 500°F)

To be used on threaded pipe connections, hydraulic pressure lines, etc. Suitable for use on lines carrying fuels (such as gasoline, diesel fuel, kerosene and aircraft oils), acids and alkalis, solvents and gases (specifications of various mediums available upon request). Because of its characteristics, Petro-Tape is far superior to other PTFE tapes for heavy-duty use. ULC Listed for sealing metal threaded pipe connections not exceeding 3" for natural gas and methane, gasoline, petroleum oils, propane and butane.

SKU #	Size
30790	1/2" x 180" roll
30791	3/4" x 180" roll
30792	1" x 180" roll
30793	1/2" x 540" roll
30794	3/4" x 540" roll
30795	1" x 540" roll
30798	1" x 540" metal roll
30800	1/2" x 540" cardboard roll

## Renew Belt Dressing



Drying time 20 minutes

Excellent for use on flat, round and V-style belt drives. Chemically stable, non-drying and water resistant for maximum efficiency. Removes residual build-up and will not glaze or collect dirt and dust. May be applied while belts are in operation.

SKU #	Size
50941	12 oz aerosol

## RuFF Heavy-Duty Rust & Corrosion Inhibitor



Operating Ranges

RuFF 21 Bulk	-2°C to 60°C (28°F to 140°F)
RuFF 9 Bulk & Aerosol	-40°C to 60°C (-40°F to 140°F)

Formulated to act as a high performance corrosion inhibitor that tenaciously adheres to all metals. Offers superior protection against water, salt water spray, calcium and chloride, oxidation and other harsh conditions. Ideal for use on construction and farm equipment, trucks, and trailers as a protective undercoating.

SKU #	Size
RuFF 21	
144120	20 liter pail
144175	205 liter drum
RuFF 9	
199120	20 liter pail
199175	205 liter drum
RuFF 9	
199141	340 g aerosol

## TF-15 Thread Sealing Compound



Operating Range -23°C to 315°C (-10°F to 600°F)

Excellent for use on all threads subject to vibration, surge, pressure and temperature fluctuations. Particularly useful in areas subject to H<sub>2</sub>S and salt water. Recommended for lines carrying a wide variety of oils, solvents, gases (except oxygen), acids, alkalis and steam. Prevents galling and thread wear, seals badly worn threads and greatly increases connection life. Seals at temperatures to 315°C and pressures to 10,000 PSI.

SKU #	Size
23002	225 ml brush top
23067	250 ml tube
23004	1 liter jar
23005	5 liter pail
23010	10 liter pail
23015	15 liter pail

## Silicone Spray Industrial Grade Lubricant



**Operating Range** -17°C to 177°C (0°F to 350°F)

Silicone Spray is a multi-purpose product that lubricates, waterproofs and protects equipment and tools. It provides high-performance lubrication and corrosion protection on locks, hinges, chains, pulleys, fans, electrical parts such as distributors, ignition wires, spark plugs and more. Silicone Spray is a professional formula that is safe for use on metal, rubber, wood, or vinyl and electrical parts. It is excellent lubricant for applications in wet environments such as automotive, aerospace, agriculture, construction, mining, oil and gas or valve maintenance.

SKU #	Size
50741	300 g aerosol

## Top-Gun Wasp & Hornet Killer



**35 KV dielectric strength**

To be used on wasps, hornets, yellow jackets and bees on HVAC equipment and enclosures, cable television equipment, telecommunications equipment, telephone and utility poles, in attics and under eaves, transformers, trees, electrical and water towers. Its trigger nozzle allows fast, accurate, dense jet stream delivery from up to 15 feet for safe application in hard to reach places.

SKU #	Size
51541	350 g aerosol

## White Lithium Grease All-Purpose Grease with PTFE



**Operating Range** -18°C to 190°C (0°F to 370°F)

To be used as a premium all-purpose grease that provides superior performance and protection for metal with moving parts, it penetrates and forms a long-lasting protective film to withstand heavy loads and high speeds, prevents rust and corrosion, eliminates squeaks and squeals and will not run or wash away.

SKU #	Size
50350	14 oz cartridge
50341	13 oz aerosol
50305	1 lb can
50316	35 lb pail
50324	120 lb keg

## Jet-Lube products listed alphabetically

12/34	Ezy-Open	Jet-Plex EP	<b>O</b>	<b>T</b>
202 Moly-Lith	Ezy-Pak 100	JetPump	OG-H	Temp-Guard
550	Ezy-Pak 115		Oven Chain Lubricant 	TF-15
769	Ezy-Pak 120	<b>K</b>		TF-500
	Ezy-Pak 125	Kiln Grease	<b>P</b>	TFW
<b>A</b>	Ezy-Turn 2	Kollar King	Petro-Tape	Top Gun
Alco EP	Ezy-Turn 3	Kopr-Kote	PFPE Grease	Tuff E Nuff
Alco-EP ECF 	Ezy-Turn 3 Arctic	Korr-Guard	Pitless Adapter Lube 	
Alco-EP 73 Plus	Ezy-Turn 4	Kovr-Kote	Plumber's Pal	<b>U</b>
AP-1 White	Ezy-Turn 5		Powr-Kote	Ultra
AP-5	Ezy-Turn 6	<b>L</b>	PS Terminal	
API-Modified Arctic	Ezy-Turn 8	Lapping Oil		<b>V</b>
API-Modified	Ezy-Turn 12	LBX -Special	<b>R</b>	V-2
Arctic Grease	Ezy-Turn 14	Lite Knight	RD-N	
AX-2	Ezy-Turn 22		RD-P	<b>W</b>
	Ezy-Turn Body Fill	<b>M</b>	Renew	Well-Guard 
<b>B</b>	Ezy-Turn H <sub>2</sub> S	Magic Wrench 	Riser Bolt Lube	White Knight 
Bullseye 	Ezy-Turn Polar	Marine Kopr	Rubber Lubricant/Mold Release	White Lithium
	Ezy-Turn PVS	Marine Moly	RuFF 9	Wire Line Lubricant ECF 
<b>C</b>		Marine MP	RuFF 21	WLD
CableLube	<b>F</b>	Marine Wire Rope & Hawser Grease	Run-N-Seal	WRL
CB-2	FMG 	Moly-Arc	Run-N-Seal ECF 	
CC-Lube 	Food Grade Silicone 	Moly-Mist	Rust Guard	<b>Z</b>
Clean-Up		Moly Petrolatum		Z-50
Clean-Up Plus	<b>G</b>	Moly-Arc	<b>S</b>	Z-Plate Aerosol
Creeper-Lube	Gear-Guard	MotherCutter 	Seal Guard	Zinc Petrolatum
	Graphite Petrolatum	MP-50	Seal-Guard ECF 	
<b>E</b>			Sheen Free 	
Easy-Clean	<b>J</b>	<b>N</b>	Silicone Compound DM	
Easy-Clean Liquid	J-75	NCS-30	Silicone Spray	
ECF Anti-Seize 	J-89	NCS-30 ECF 	Silver Plus	
Eco-Safe 	JL-5000 	Nikal	SS-30	
EMS 	Jacking System Grease ECF 	Nikal Nuclear		
Enviro-Guard 	Jet-Lok PS-50	No. 33		
Enviro-Safe	Jet-Lok PS-67	No. 60		
EP Bearing Grease	Jet-Lok TL-72	Nuclear Nonmetallic		
Extreme	Jet-Lube 21			



Qualifying products will bear the thumbprint.

[www.jetlubecanada.com](http://www.jetlubecanada.com)



## CONTACT US

### Head Office

3820-97 Street NW  
Edmonton, Alberta T6E 5S8

Toll Free Ph: 1-888-771-7775  
Local Phone: (780) 463-7441

Toll Free Fax: 1-888-449-4449  
Fax: (780) 463-7454

[sales@jetlubecanada.com](mailto:sales@jetlubecanada.com)  
[www.jetlubecanada.com](http://www.jetlubecanada.com)

Vice President & General Manager  
Gary McCormick  
[garym@jetlubecanada.com](mailto:garym@jetlubecanada.com)

National Sales & Marketing Manager:  
Jim McLaws  
[jdm@jetlubecanada.com](mailto:jdm@jetlubecanada.com)

Technical Service:  
Neil Ruel  
[neilr@jetlubecanada.com](mailto:neilr@jetlubecanada.com)

Inside Sales:  
Maleena Carreiro  
[maleenab@jetlubecanada.com](mailto:maleenab@jetlubecanada.com)



Copyright©2012 - All images, photographs, logos and content are the property of Jet-Lube Inc. and Jet-Lube of Canada Ltd. These files are provided for information only and cannot be altered, disseminated or used in any way except by express permission of Jet-Lube of Canada Ltd.

