

# METAL CUTTING SAWS

## CUTTING DEPTH 3 1/4" - 4 3/4"

67 - 120 mm

### HAND DRY CUTTER CIRCULAR SAW 8230N

Include Ø 9" / 230 mm / 48T saw blade - Ref. 608280IUS

Cutting depth  3 1/4" / 82 mm

### HAND DRY CUTTER 18V CIRCULAR SAW 8203E

Include Ø 8" / 203 mm / 48T - Ref. 608295ENA

Cutting depth  2 5/8" / 67 mm



MADE  
IN  
GERMANY

### SUPER HAND DRY CUTTER 8320

Include Ø 12 5/8" / 320 mm / 84T - Ref. 608270US

Cutting depth  4 3/4" / 120 mm  
(on guide-rail)







**SUPER HAND DRY CUTTER 12-5/8"**  
**8320 - THE BIGGEST**



**Technical specifications**

Power input	16 amp
Voltage	115V / 60Hz
No load speed	1,700 RPM
Weight	18.5 lb
Blade size	Ø 12-5/8"
Bore	Ø 1"
Cable length	5 m

**Max. cutting capacities (90°)**

Round	4-3/4" x 1/4"
Square	4-3/4" x 4-3/4" x 1/4"
Rectangular	4-3/4" x 1/4"

**Super hand dry cutter 8320**

**Art.**

With Ø 12-5/8" / 84T saw blade	608270US
With Ø 12-5/8" / 84T saw blade & 4' 7" guide rail & 2 quick release clamps	608270USET

**Carbide tipped saw blades**

**Art.**

Ø 12-5/8" / 84T - for sandwich panels and steel	608276
Ø 12-5/8" / 72T - for thick walled material	608278
Ø 12-5/8" / 84T - for steel, stainless steel - coated food and construction	608276NSF



**HAND DRY CUTTER 9"**  
**8230N - THE AGILE**



**Technical specifications**

Power input	15 amp
Voltage	115V/60Hz
No load speed	2,600 RPM
Weight	16 lb
Blade size	Ø 9"
Bore	Ø 1"
Cable length	5 m

**Max. cutting capacities**

	90°	45°
Round	3-1/4" x 3/16"	2-3/16" x 1/8"
Square	3-1/4" x 3/16"	2-3/16" x 1/8"
Rectangular	3-1/4" x 3/8"	2-3/16" x 5/32"
Sheet metal	3/8"	5/16"

**Hand dry cutter 8230N + case**

**Art.**

With Ø 9" / 48T saw blade for stainless steel	608280IUS
<b>Carbide tipped saw blades</b>	<b>Art.</b>
Ø 9"/48T - for standard steel	72123048
Ø 9"/48T - for steel & stainless steel	72123048I
Ø 9"/48T - steel & stainless steel - coated food & construction	72123048NSF
Ø 9"/60T - for aluminum	72123060
Ø 9"/68T - for thin walled material	72123068
Ø 9"/84T - for thin sheet	72123084
Ø 9"/60T - "LBS impact resistant" metal grids	72223060



**DRY MITER CUTTER 10"**  
**9410 ND - THE VERSATILE**

**Technical specifications**

Power input	14 amp
Voltage	115V/50Hz
No load speed	1,600 RPM
Weight	42 lb
Blade size	Ø 10"
Bore	Ø 1"
Cable length	2.5 m

**Dry miter cutter 9410 ND**

**ART.**

With Ø 10"/60T saw blade for unalloyed (thin-walled) steel and 1" shafts	600651
--	--------

<b>Carbide tipped saw blades</b>	<b>Art.</b>
Ø10' / 60T - for steel & stainless steel	600598
Ø10' / 66T - for stainless steels & steel, food & construction	600654NSF
Ø10' / 66T - for metal grids & grates	72225566
Ø10' / 66T - for thin walled steel	600654
Ø10' / 80T - for aluminum	600655A



**CORDLESS HAND DRY CUTTER 8"**  
**8203E - THE INDEPENDENT**



**Technical specifications**

Power input	18 V
No load speed	3,500 RPM
Weight	12 lb
Blade size	Ø 8"
Bore	Ø 1"

**Max. cutting capacities**

	90°	45° (Bevel cut)
Round	2-5/8" x 1/4"	1-5/8" x 1/4"
Square	2-5/8" x 2-5/8" x 1/4"	1-5/8" x 1-5/8" x 3/16"
Rectangular	2-5/8" x 1/4"	1-5/8" x 1/4"
Sheet metal	3/8"	5/16"

**Cordless hand dry cutter 8203E**

**Art.**

incl. Ø 8"/48T "LBS impact resistant" saw blade for steel, 2 high performance 18V LiHD 5,5A batteries, Air-cooled LiHD high speed loading station 110V & carry case	608295ENA
---	-----------

**Carbide tipped saw blades**

**Art.**

Ø 8" / 48T "LBS impact resistant" - for thin-walled steel	72220348
Ø 8" / 54T - for stainless steel	72120354I



**PREMIUM PORTABLE CUT-OFF SAW 14"**  
**9435 - THE MONSTER!**



**Technical specifications**

Power input	21 amp
Voltage	115V/50Hz
No load speed	1,400 RPM
Weight	56 lb
Blade size	Ø 14"
Bore	Ø 1"
Cable length	2.5 m

**Max. cutting capacities**

	90°	45°
Round	5-1/2" (inox: 5")	4"
Square	5" x 5"	3-1/8" x 3-1/8"
Rectangular	4-1/8" x 5-1/2"	3" x 4"

**Premium super dry cutter 9435**

**Art.**

With Ø 14" / 90T saw blade for steel & stainless steel	600560UST3
<b>Carbide tipped saw blades</b>	<b>Art</b>
Ø 14" / 120T - for steel & stainless steel (extra thin)	600512I
Ø 14" / 90T - for steel & stainless steel (thin)	600570
Ø 14" / 90T - for steel & stainless steel coated	600570NSF
Ø 14" / 72T - for steel & stainless steel (medium)	600580
Ø 14" / 60T - for steel & stainless steel (thick)	600590
Ø 14" / 60T - for cast iron	600591
Ø 14" / 96T - for aluminum	600594



**Max. cutting capacities**

	90°	45°
Round	2-3/4" x 1/8"	2-3/8" x 1/8"
Square	2-3/4" x 2-3/4" x 1/8"	2-3/8" x 2-3/8" x 1/8"
Rectangular (without clamping system)	4" x 2-3/4" x 1/8"	2-3/8" x 2-3/8" x 1/8"

